



TVW-1101

1.3 MPX HD IR Wedge Dome, IP66, PAL

Overview

TruVision™ TVW-1101 IR Wedge dome camera bring the state-of-the-art, and high definition pictures to the mass video surveillance market. This camera has IR and True Day/Night as standard. Together with local storage will this IP cameras represent a flexible video surveillance device that meet any need. Equipped with advance technology and signal processing capabilities, the effectively capture video under challenging conditions.

Compression & streaming

The TruVision camera uses H.264 compression technology with dual-stream capability, making it easy to manage the camera's bandwidth usage.

Fully designed to adhere to PSIA and ONVIF open communication standards as well as supporting a CGI command set, these cameras allow for simple integration into any IP system. Video streams can be set up for high or low bandwidth, and images can be streamed for live viewing or sent to a designated recording location.

Form Factor

This Wedge dome version provides a vandal-proof solution. By default it is IP66 rated so it can be used for outdoor installations as well indoor. Its unique design makes this camera discreet and aesthetically attractive.



Standard Features

- Maximum Resolution: 1280x960 @ 25fps
- Maximum Real Time Resolution: 1280x960 @ 25 fps
- Real time HD 960p
- Designed to PSIA and ONVIF open standards
- H.264 compression with dual streaming functionality
- 1/3" CMOS image sensor
- True Day/Night
- IR up to 10m
- 2.8mm fixed lens
- IP66 rated
- Edge recording up to 64GB

TVW-1101

1.3 MPX HD IR Wedge Dome, IP66, PAL

Specifications

Camera

Sensor Size:	1/3"
SD / MPX:	1.3MPX
Sensor scan:	Progressive Scan
Sensor type:	CMOS
IP Compression / Standard:	Main stream: H.264 Sub stream: H.264/MJPEG
Maximum Resolution (@ FPS):	1280 x 960 @25 fps
Maximum Real Time Resolution:	1280 x 960
HD 720p:	Yes
Full HD 1080p:	No
Digital S/N ratio:	50dB
Electronic shutter:	1/25s to 1/100.000s
Certification:	UL, CE, FCC, C-tick, REACH, RoHS, HALT, WEEE

Lighting performance

Wide Dynamic Range:	DWDR
WDR in dB:	72dB
Digital noise reduction:	3D DNR
Day/Night:	True Day/Night
Motorized IR Cut Filter:	Yes
Color sensitivity:	0.01 lux @ F1.2
B/W sensitivity:	0 Lux with IR
IR sensitivity:	0 Lux with IR
IR Range:	Up to 10m
IR Wavelength:	850nm
B/W trigger:	4.12lux
IR trigger:	4.12lux

Housing

Camera type:	Wedge
IP rating:	IP 66
Outdoor:	Yes
Rugged:	IK08 Rating

Lens

Control type:	Fixed
Optical zoom:	No
Focal length:	2.8mm
F-stop:	2
Autoiris:	No
Varifocal:	No
Zoom lens:	No
Autofocus:	No

Power consumption

Voltage Input:	12VDC \pm 10%
Current:	Max. 0.42A
Power Consumption:	Max. 5W
PoE:	PoE(802.3af)

Network

ONVIF:	2.2
PSIA:	1.1
CGI:	Yes
Network Protocols:	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP, 802.1x, Qos, IPv4/IPv6

Local Storage

Media:	Built-in Micro SD/SDHC/SDXC card slot
Capacity:	64GB

Camera Analytics

Motion Detection:	Yes
Privacy Masking:	4



Mechanical / Environmental

Dimensions:	99 x 97 x 53mm (3,86 x 3,82 x 2,09 in)
Weight:	407g (0.89lb)

Cold start Temperature	-20°C (-14°F)
Operating Temperature:	-30°C to 60°C (-22°F to 140°F)

Ordering Information

Part No.	Description
TVW-1101	1.3 MPX HD IR Wedge Dome, IP66, PAL



Unit: mm

