



TVP-1104

TruVision™ 2 MPX Full HD Pendant 20X PTZ dome, PAL

Overview

TruVision IP Full HD 2 MPX PTZ gives you a full-functional dome that allows you to enjoy all the benefits of a PTZ solution in high definition.

PTZ technology

This series of H.264 PTZ solutions makes use of the latest available technology that allows the dome to be installed in a wide range of applications and environmental conditions. They are available with IP66-rated standard outdoor pendant housings as well as flush and surface-mount indoor housings. This latest PTZ solution is equipped with high quality progressive scan imaging technology.

Compression & streaming

The TruVision Full HD IP PTZ camera uses H.264 compression technology with dual-streaming capability, making it easy to manage the camera's bandwidth usage. Fully designed to adhere to the ONVIF and PSIA open communication standards as well as supporting a CGI command set, the camera allows for simple integration into any IP system. Video streams can be set up for high or low bandwidth, and images can be streamed for live viewing or sent to a designated recording location.

Additional Features

ROI - This feature helps you to optimize image bandwidth and storage. You can select an important area of detail or ROI (Region of interest) in a stream, such as a number plate or face. The ROI area will have a higher quality image and the non-ROI areas will have a lower image quality thereby saving bandwidth.

Intelligent tracking - This is used to track a moving object or person in a selected region.



Standard Features

- 1/3" Progressive Scan CMOS
- 2 MPX Full HD sensor
- Full HD 1080p Real-Time
- H.264 Advanced compression technology
- ONVIF/PSIA/CGI compliant
- Models include 7 alarm inputs and 2 relay output
- 256 preset positions, 8 preset tours and 4 shadow tours
- 360° endless rotation
- 540°/s Pan Preset Speed and 400°/s Tilt Preset Speed
- Auto-flip image
- Intelligent tracking
- ROI encoding of a selected area in the image
- Built-in SDHC card slot
- For pendant mount
- Bracket is not included
- IP66 rated
- Compatible with GEA and UVP accessories

TVP-1104

TruVision™ 2 MPX Full HD Pendant 20X PTZ dome, PAL

Specifications

Camera

Sensor Size:	1/3"
SD / MPX:	2 MPX
Sensor scan:	Progressive Scan
Sensor type:	CMOS
IP Compression/Standard:	Main stream: H.264 Sub stream: H.264/MJPEG
Available Resolutions:	Main stream: 1920x1080,1280x960,1280x720 Sub stream: 704x576,352x288,176x14
Maximum Resolution (@ FPS):	1920x1080 @25 fps
Maximum Real Time Resolution:	1920x1080
HD 720p:	Yes
Full HD 1080p	Yes
Composite Output (BNC):	Yes, 1 BNC
Digital S/N ratio:	50dB
Electronic shutter:	1/25s to 1/100.000s
Certification:	UL, CE, FCC, C-tick, REACH, RoHS, HALT, WEEE

Lighting performance

Wide Dynamic Range:	DWDR
WDR in dB:	NA
Digital noise reduction:	3D DNR
Day/Night:	True Day/Night
Motorized IR Cut Filter:	Yes
Color sensitivity:	0.05 lux @ F1.6, 1/1s, AGC ON
B/W sensitivity:	0.005 lux @ F1.6, 1/1s, AGC ON
B/W trigger:	1lux

Housing

Camera type:	Pendant mount
IP rating:	IP66
Outdoor:	Yes
Vandal-Resistant	comes with (IK10) vandal proof bubble:

PTZ

Pan:	Pan Manual Speed: 0.1° -300°/s, Pan Preset Speed: 540°/s
Tilt:	Tilt Manual Speed: 0.1°-240°/s, Tilt Preset Speed: 400°/s
Endless Pan:	360°endless
Auto-flip:	Auto Flip
Optical zoom:	20X
Digital zoom:	16X
Presets:	256

Lens

Focal length:	4.7-94mm
F-stop:	F1.6 - F3.5
Autoiris:	Yes
Varifocal:	Yes
Zoom lens:	20x
Autofocus:	Yes

Power consumption

PSU included:	No
Voltage Input:	24VAC
Current:	PoE+: Max. 0.5A 24VAC: Max. 2.7A
Power Consumption:	PoE+: Max. 25 W 24VAC: Max. 65 W
PoE:	PoE+(802.3at)

Network

ONVIF:	2.2
PSIA:	1.1
CGI:	Yes
Network Protocols:	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP, 802.1x, Qos, IPv4/IPv6

Local Storage

Media:	Built-in SD/SDHC Slot
Capacity:	up to 32GB

Audio

Audio:	2-way Audio
Built-in microphone:	No
Audio compression:	G.711/G.726

Camera Analytics

Motion Detection:	Yes
Privacy Masking:	24

Alarm

Alarm Input:	7
Alarm Output:	2

Mechanical/ Environmental

Dimensions:	Ø 220 × 266 mm (Ø 8.66 × 10.5 in)
Weight:	3.5 kg (7.7lb.)
Operating Temperature:	PoE+: -30 to 65°C 24VAC: -40°C-65°C
Cold start Temperature:	PoE+: -30°C 24VAC: -40°C

Accessories

Brackets:	GEA, UVP
Power Supplies:	ATD-6814-PSU

Ordering Information

Part No.	Description
TVP-1104	TruVision™ 2 MPX Full HD Pendant 20X PTZ dome, PAL

